



Euroanvil Specifications

1. Material: C=0.3%, Mn=1.3%, Si=0.5%
According to factory norm/standard (manganese iron)
2. Tolerance of weight is 10% according to the norms
3. Hardened shift is up to 1/3 of the high of the anvil
Hardness: min 420 HB (44 HRC)
4. Tolerance of HARDY HOLES
 up to 20 x 20 mm +/- 2mm
 20 x 20 to 30 x 30 mm +/- 4 mm
5. Tolerance of PRITCHEL HOLES
 +/- 0.5
6. Curve of working surface is up to 5 mm max.
7. Roughness of working surface Ra = 3,2
8. It is highly recommended to use the hammer weight of which does not exceed the weight proportion of 1:30 anvil to hammer.



EuroAnvil available in the following sizes:

Weight	Length	Height	Face Width	Hardie	Pritchel
175 lb.	26	11.5	4	1	1.63
335 lb.	34	12.8	5.25	1	1.63
500 lb.	43	14.6	5.75	1	1.63

Euroanvils.net

German Pattern available in the following sizes:

Weight	Length	Height	Face Width	Hardie	Pritchel
119 lb.	22.4	9.6	4.1	1.18	.88
167 lb.	24.8	10.6	5	1.18	.88
260 lb.	29.1	12.6	5.4	1.18	.88



With our great discount on shipping these are really affordable anvils. Join the list of satisfied customers. Call or email to reserve your new anvil now. Email jelliott@blacksmithsupply.com or call us at 1-877-EUROANVILS. See www.euroanvils.net for current prices.